



+ View More

PRODUCT NUMBER: 1005318

ME82 - Manyard Shock absorbing Lanyard - 2m - 2 ML00

Complete 2m with 2 galvanised connectors (ML00)

Overview

Reference Number

1005318

Product Type

Fall Protection

Range

Shock Absorbing Lanyards

Line

n/a

Brand

Miller by Sperian

Brand formerly known as

MILLER

Industry

● Industry ● Building and Construction

Product Use

2m Shock absorbing Lanyard - complete with 2 galvanised connectors (ML00), with TEFLON finish

Added elasticity 32%
Integrated shock absorber
Highly resistant external webbing, Teflon finish
Warning flag
2 Screw karabiners
Security Clip

Features & Benefits**Feature**

A unique stretchable design. A safety clip that straps on to the harness to hold the Manyard when not in use. Special woven shock-absorbing inner core. Heavy tubular outer jacket. Unique warning flag which provides visual proof that a lanyard has been involved in a fall and should be removed from service. Reliable visual inspection: the integral res core becomes visible if the outer jacket is damaged or worn. The TEFLON hi-tech protective finish on the outer tubular jacket prolongs the service life of the Manyard.

Benefit

Lightweight and easy to use, the elasticated manyard is ideal for maintenance on cranes or granties. When contracted the elasticated shock-absorbing lanyard reduces the risk of tripping or snagging. The unique woven shock-absorbing material reduces fall arrest forces.

Technical Description**Length**

2m

Weight

0.675 Kg

Breaking Strength

> 15 KN

Operating Temperature

-30°C to +50°C

Webbing**Webbing Raw Material**

Polyamide

Webbing Breaking Strength

> 2200 daN

Connector**Connector Type**

TypeML00

Connector Raw Material

Raw MaterialGalvanized steel

Connector Opening

Opening18 mm

Connector Breaking Strength

Breaking Strength> 2500 daN

Connector Standard

StandardEN 362

Energy Absorber**Energy Absorber Raw Material**

Polyester fibers


Energy Absorber Breaking Strength

> 500 daN

Complementary Information

Elasticity : 32.5 % Length Folded : 1.35m Integrated shock absorber Polyester fibers Impact strength reduction: > 500 daN External highly resistant webbing: Polyamide webbing 45mm - green Teflon finish Breaking strength: > 2200 daN

Certifications

 **E.C. Declaration of Conformity**

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

333

EC Attestation Number

0082/490/160/04/01/0089 EXT N°01/10/08

Photos & Images

We're sorry, there are no images available at this time.

Packaging

EAN Code

7312550053188

Honeywell

[View other region sites](#)

© 2011 Honeywell International Inc.