Honeywell



PRODUCT NUMBER: 1005325

ME86 - Manyard Shock absorbing Lanyard - 2m - ML00+ML04

Complete 2m with 1 galvanised connector and 1 snap hook 63mm.

Overview

Reference Number

1005325

Product Type

Fall Protection

Range

Shock Absorbing Lanyards

Line

n/a

Brand

Miller by Sperian

Brand formerly known as

MILLER

Industry

Industry
Building and Construction

Product Use

2m Shock absorbing Lanyard - complete with 1 screwgate karabiner (ML00) & Automatic Snap hook, with TEFLON finish

Added elasticity 32%

Integrated shock absorber

Highly resistant external webbing, Teflon finish

Warning flag

1 Screw karabiner and 1 Automatic Scaff hook

Security Clip

Features & Benefits

Feature

A unique stretchable design. A safety clip that straps on to the harness to hold the Manyard when not in use. Special woven shock-absorbing inner core. Heavy tubular outer jacket. Unique warning flag which provides visual proof that a lanyard has been involved in a fall and should be removed from service. Reliable visual inspection: the integral res core becomes visible if the outer jacket is damaged or worn. The TEFLON hi-tech protective finish on the outer tubular jacket prolongs the service life of the Manyard.

Benefit

Lightweight and easy to use, the elasticated manyard is ideal for maintenance on cranes or granties. When contracted the elasticated shock-absorbing lanyard reduces the risk of tripping or snagging. The unique woven shock-absorbing material reduces fall arrest forces.

Technical Description

Length

2m

Weight

0.985 Kg

Breaking Strength

> 15 KN

Operating Temperature

-30°C to +50°C

Webbing

Webbing Raw Material

Polyamide

Webbing Breaking Strength

> 2200 daN

Connector

Connector Type

TypeCS20

Connector Raw Material

Raw MaterialZinc-plated steel

Connector Opening

Opening18 mm

Connector Breaking Strength

Breaking Strength> 2500 daN

Connector Standard

StandardEN 362

Connector

Connector Type

TypeSnap hook

Connector Raw Material

Raw MaterialWhite chromate steel

Connector Opening

Opening65 mm

Connector Breaking Strength

Breaking Strength> 2200 daN

Connector Standard

StandardEN 362

Energy Absorber

Energy Absorber Raw Material

Polyester fibers

Energy Absorber Breaking Strength

> 500 daN

Complementary Information

Elasticity 32,8 % Length Folded 1.35m External highly resistant webbing Polyamide webbing 45mm - green Teflon finish Breaking strength: > 2200 daN

Certifications

■ E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

333

EC Attestation Number

0082/490/160/04/01/0089 EXT N°01/10/08

Photos & Images

We're sorry, there are no images available at this time.

Packaging

EAN Code

7312550053256

Honeywell

View other region sites © 2011 Honeywell International Inc.