



+ View More

PRODUCT NUMBER: 1005326

ME83 - Manyard Shock absorbing Lanyard

Complete 1,5m with 1 galvanised connector and 1 snap hook 22mm

Overview

Reference Number
1005326

Product Type
Fall Protection

Range
Shock Absorbing Lanyards

Line
n/a

Brand
Miller by Sperian

Brand formerly known as
MILLER

Industry

- Industry
- Building and Construction

Product Use
1.5m Shock absorbing Lanyard - complete with 1 screwgate karabiner (ML00) and Automatic karabiner, with TEFLON finish
Added elasticity 32%
Integrated shock absorber
Highly resistant external webbing, Teflon finish Warning flag 1 Screw karabiner and 1 Automatic karabiner
Security Clip

Features & Benefits

Feature

A unique stretchable design. A safety clip that straps on to the harness to hold the Manyard when not in use. Special woven shock-absorbing inner core. Heavy tubular outer jacket. Unique warning flag which provides visual proof that a lanyard has been involved in a fall and should be removed from service. Reliable visual inspection: the integral res core becomes visible if the outer jacket is damaged or worn. The TEFLON hi-tech protective finish on the outer tubular jacket prolongs the service life of the Manyard.

Benefit

Lightweight and easy to use, the elasticated manyard is ideal for maintenance on cranes or gantries. When contracted the elasticated shock-absorbing lanyard reduces the risk of tripping or snagging. The unique woven shock-absorbing material reduces fall arrest forces.

Technical Description

Length

1.05m

Weight

0.650 Kg

Breaking Strength

> 15 KN

Operating Temperature

-30°C to +50°C

Webbing

Webbing Raw Material

Polyamide webbing 45mm - green

Webbing Breaking Strength

> 2500 daN

Connector

Connector Type

Karabiner

Connector Raw Material

Zinc-plated steel

Connector Opening

17 mm

Connector Breaking Strength

> 2200 daN

Connector Standard

EN 362

Connector

Connector Type

Snap hook

Connector Raw Material

ME83 - Manyard Shock absorbing Lanyard - 1005326

Chromated steel

Connector Opening

20mm

Connector Breaking Strength

>2200daN

Connector Standard

EN362

Complementary Information

Elasticity 32.8 % Integrated shock absorber Polyester fibers Impact strength reduction: > 500 daN

Certifications

E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0333 AFAQ/CTH

EC Attestation Number

0082/490/160/04/01/0089 EXT N°01/10/08

Photos & Images

We're sorry, there are no images available at this time.

Packaging

EAN Code

7312550053263

Honeywell

[View other region sites](#)

