

PRODUCT NUMBER: 1785010

## Aluminium Filter 250 A2



+ View More

### Overview

#### Reference Number

1785010

#### Product Type

Respiratory Protection

#### Range

Reusable APR

#### Brand

Sperian

#### Brand formerly known as

FERNEZ by Willson

#### Industry

• Industry

#### Product Use

The A2 filter is used for protection against type A toxic gases according to the EN 141:2000 standard (i.e. organic gases and vapours).

This filter is used with a Sperian full-face mask using an RD 40 connector.

The full-face mask and A2 filter set must only be used when the toxic concentration is less than 2000 x TLV.

(TLV= TWA for 8 hours of work or STEL for 15 minutes of work)(cf. INRS document ed. 780 "Respiratory protection devices").

**They can only be used in sufficiently ventilated premises where the atmosphere**

**contains a minimum oxygen volume of 17 %.**

**CHARACTERISTICS :**

- Type 250 cc
- Lightweight and resistant aluminium alloy housing with plastic cover- 106 mm in diameter
- Does not obstruct the field of vision
- EN 148-1 conforming threaded connection to the Sperian full-face mask, ensuring a reliable connection and an excellent seal
- Activated coconut carbon
- Very high absorption efficiency.

**GASES TESTED :**

- Carbon tetrachloride (CCl<sub>4</sub>)
- The concentration by volume of the test gas is 0.5%
- The tested air flow is 30 litres per minute
- Minimum duration required before "breakthrough": 40 min.

**PACKAGING :**

Packaged in individual cardboard boxes.

In case of a claim on this product, please indicate the lot number shown on the label.

**Features & Benefits**

**Feature**

Aluminium casing

**Benefit**

- Less of an impact from external shocks - Memory of shocks – physical 'tell-tale'

**Feature**

Coconut based carbon

**Benefit**

Optimal period of use

**Feature**

P3 filter

**Benefit**

Constant optimal filtration

**Feature**

Filter structure

**Benefit**

Lower breathing resistance – less user fatigue

**Feature**

Service life

**Benefit**

Product offering quality and the possibility of safe storage between periods of use

**Feature**

Tightness test

**Benefit**

Wearer safety

**Feature**

Packaging

**Benefit**

- Safe - Easy storage

**Certifications**

**EC Category PPE**

3


**Quality Assurance**

ISO 9001 / 2000

**EC Certificate Number**

0070-236-079-10-03-0080

**EC Attestation**

 EC Attestation

**EC Attestation Number**

0070-236-079-10-03-0080

**Photos & Images**

We're sorry, there are no images available at this time.

**Honeywell**

For general inquiries  
800.343.3411

View other region sites  
© 2011 Honeywell International Inc.