



## SAFE Polycarbonate clear

### 20930-001

The SAFE polycarbonate visor is the best selection for resistance to impact. It is designed to be combined with all SAFE carriers, SECURE earmuffs and a variety of helmets for a full above the neck protection.

The visor is approved to medium impact and is suitable for applications such as grinding, construction work and general industry work.

#### Technical data

Type/Material	Clear polycarbonate
Thickness	1 mm
Weight	74 g
Length	200 mm
Approvals	CE EN 166 1B39, EN 170 2-1,2 ANSI Z87+, CSA Z94.3-2007

#### Standards

EN 166:2001 European standard for eye protection  
ANSI Z87.1-2003 The American National Standard for Eye and Face Protection  
CSA Z94.3-2007 The Canadian Standard for Eye and Face Protection

#### EN 166 visor markings

1: optical rating class  
B: protection from medium energy impacts  
3: protection from liquid splashes  
9: resistance to molten metal droplets and penetrations of hot solids

#### Additional visor approvals and markings

EN 170/2-1,2: UV scale number

#### ANSI visor markings

Z87+ Basic and high impact protection

#### Approvals

This visor is in compliance with the PPE regulation 2016/425 and other appropriate directives to fulfil the requirements of CE marking. The full text of the EU declaration of conformity is available at following internet address: [www.hellbergsafety.com/doc](http://www.hellbergsafety.com/doc).

#### Compatible with

20902-001	SAFE 1 carrier
20901-001	SAFE2 standard carrier
20901-010	SAFE2 standard low peak carrier
20901-501	SAFE2 flex carrier
20901-510	SAFE2 flex low peak carrier
61100-001	SAFE 3 carrier