



## SAFE Polycarbonate chinguard 20939-001

The SAFE polycarbonate chinguard visor is the best selection for resistance to impact. A chinguard is recommended when dealing with chemicals. It is designed to be combined with earmuffs, helmets and carriers for a full above the neck protection.

The visor is approved to medium impact and is suitable for applications such as grinding, construction work and general industry work.

### Technical data

Type/Material	Polycarbonate clear
Thickness	1 mm
Weight	110 g
Lenght	220 mm
Approvals	CE EN 166 1B39, EN 170 2-1,2

### Standards

EN 166:2001 European standard for eye protection

### EN 166 visor markings

- 1: optical rating class
- B: protection from medium energy impacts
- 3: protection from liquid splashes
- 9: resistance to molten metal droplets and penetrations of hot solids

### Additional visor approvals and markings

EN 170/2-1,2: UV scale number

### Approvals

This visor is in compliance with the PPE regulation 2016/425 and other appropriate directives to fulfil the requirements of CE marking. The full text of the EU declaration of conformity is available at following internet address: [www.hellbergsafety.com/doc](http://www.hellbergsafety.com/doc).

### Compatible with

20902-001	SAFE 1 carrier
20901-001	SAFE2 standard carrier
20901-010	SAFE2 standard low peak carrier
20901-501	SAFE2 flex carrier
20901-510	SAFE2 flex low peak carrier
61100-001	SAFE 3 carrier