

Product Datasheet model skyguard NT 9175 260

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

Product characteristics	* An improved spectacle with all-round protection * An injection moulded TPU frame increase wearer protection levels through minimising the risk of particle ingress * The flexible, closed-pore soft components enables a customised, individual fit * Easy to clean to promote long term use * Comfortable, customized fit by individual side arm inclination and length adjustment
Technical details Frame Material Colour Material Colour	Front piece PP blue TPU layer TPU grey

Manufacturer's ID code	Marking W
Applicable EN norm	166
Fiedl of use	3 (drops and splashes of liquid) 4 (large dust particles)
Low-energy impact	F (45 m/s)
Conformity symbol	CE
Material	Side piece PBT+PC
Features	adjustable inclination
Colour	blue
Material	Temple PP
Features	adjustable to four different lengths
Colour	blue
Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
No. of certificat. body	0196
Lens	
Material	PC
Thickness	2,1 mm
Coating	supravision HC-AF
Colour	clear

Filter	Marking
Manufacturer's ID code	2-1,2 (DIN EN 170)
Optical class	W
Low-energy impact	1
Surface resistance to fine particles	F (45 m/s)
Antifog	K
Tested acc. to DIN	N
Conformity symbol	DIN
	CE
Miscellaneous	
Weight	42 g
Packing	5 spectacles
	160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170