



PRODUCT NUMBER: 1032875
Miller H-Design® DuraFlex™
2pts Harness Auto Front
D-ring -Size 1

Miller H-Design® DuraFlex™ 2 points harness with automatic buckles on chest and legs straps and provided with a front 2 D-ring at the sternal point. Size 1



Overview

Reference Number

1032875

Product Type

Fall Protection

Range

Harness

Brand

Miller by Honeywell

Industry

- Building and Construction
- General Industry
- Telecoms
- Utilities

Product Use

The Miller H-Design® harnesses are the new generation of harnesses dedicated to construction and general industry sectors providing more comfort, freedom of movements and safety to workers.

Features & Benefits

Feature

Shoulder Straps : Duraflex Stretch 44,5 mm webbing PES with PTFE treatment (water repellent / anti stain) Colour : green with a black drawing Breaking strength :> 2200 daN

Feature

Other Straps : Standard black webbing 44 mm PES with PTFE treatment (water repellent / anti stain) Breaking strength : > 2700 daN

Feature

Back Anchorage D-ring : Material : steel Finish : Zinc plated Silver Breaking strength : > 2300 daN

Feature

Sternal point : D ring. Material : steel Finish : Zinc plated Breaking strength : > 2 800

Feature

Aluminium automatic buckles : Breaking strength : > 900 daN

Feature

Steel mating buckles : Finish : Zinc plated Silver Breaking strength : > 900 daN

Feature

Weight : 1,18 Kgs Breaking strength:> 15 KN Temperature: -30°C to +50°C EN 361 Full Body Harnesses

Feature

Certified for maximum load of 140 Kgs

Certifications

 E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Attestation

 EC Type examination certificate 1032874-1032875-1032876-1032877

EC Attestation Number

0082/490/160/05/14/0156

Certifications

- EN 361

Literature & Documents

1032874-1032875-1032876-1032877 Data Sheet EN

http://www.honeywellsafety.com/supplementary/documents_and_downloads/fall_protection/full_body_harness/4294983959/1033.aspx

Photos & Images

1032874_1032875_1032876_1032877_Miller_H-Design-Duraflex-harness-side-290x325

<http://www.honeywellsafety.com/assets/0/324/936/944/906bcba4-d7b0-4080-b61f-04e7e2839e6b.jpg>

Additional Information

User Manual

NT90023600 IND B

Maintenance

Life Cycle

Life expectancy of our harnesses is 10 years from the date of manufacture.

Storage Information

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Care Instructions

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.

Packaging

EAN Code

63079098

Country of Origin

France